

Amendments to the Claims

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A biopsy device suitable for use with a magnetic resonance imaging machine, said device comprising an elongated needle for receiving tissue therethrough, the needle comprising:

a distal needle segment comprising a tissue receiving port, the distal needle segment formed of a non-metallic, first material that does not interfere with MRI imaging of a portion of the distal needle segment associated with the tissue receiving port; and

a proximal needle segment disposed proximally of the tissue receiving port, the proximal needle segment formed at least in part of a metallic, second material different from said first material;

wherein the proximal needle segment and the distal needle segment provide at least one substantially continuous lumen, wherein the proximal needle segment and the distal needle segment are longitudinally joined along a common axis; and

wherein a portion of the proximal needle segment extends distally of the proximal end of the distal needle segment.

2. (canceled)

3. (canceled)

4. (previously amended) The device of Claim 1 wherein a portion of the distal needle segment is molded over a portion of the proximal needle segment.

5. (canceled)

6. (canceled)

7. (canceled)

8. (original) The device of Claim 1 wherein the second material is selected from the group comprising aluminum, aluminum alloys, stainless steel, titanium, titanium alloys, and combinations thereof.

9. (original) The device of Claim 1 further comprising a distal piercing tip disposed distal of the tissue receiving port.
10. (original) The device of Claim 9 wherein the distal piercing tip comprises a non-metallic material.
11. (original) The device of Claim 9 wherein the distal piercing tip comprises a material selected from the group comprising ceramics and glasses.
12. (original) The device of Claim 1 wherein the proximal needle segment and the distal needle segment provide a continuous, smooth cutter lumen.
13. (original) The device of Claim 1 wherein the proximal needle segment and the distal needle segment provide a continuous vacuum lumen.
14. (previously amended) The device of Claim 13 wherein the needle comprises at least one passage extending from the vacuum lumen to an outer surface of the needle.
15. (original) The device of Claim 14 wherein the distal needle segment comprises a plurality of passages extending from the vacuum lumen to the outer surface of the needle.
16. (previously amended) A biopsy device suitable for use with a magnetic resonance imaging machine, said device comprising:
a distal needle segment comprising a tissue receiving port communicating with a distal cutter lumen portion, the distal needle segment formed of a first non-metallic material; and
a proximal needle segment formed at least in part of a metal, the proximal needle segment comprising a proximal cutter lumen portion, and wherein said metal is spaced proximally at least about 0.5 inch from a proximal edge of said tissue receiving port;
wherein the distal needle segment is coupled with the proximal needle segment, wherein the distal cutter lumen portion is longitudinally coupled with the proximal cutter lumen portion along a common axis.

17. (previously amended) The device of Claim 16 wherein said metal is spaced between about 0.5 inch and about 2.5 inches from a proximal edge of said tissue receiving port.

18. (previously amended) The device of Claim 16 wherein said metal is spaced between about 0.5 inch and about 1.5 inch from a proximal edge of said tissue receiving port.

19. (previously amended) A biopsy device suitable for use with a magnetic resonance imaging machine, said device comprising an elongated needle for receiving tissue therethrough, the needle comprising:

- a distal needle segment formed of a non-metallic material and having a lateral tissue receiving port communicating with a distal cutter lumen segment, wherein the distal needle segment has a proximal end; and

- a metallic proximal needle segment disposed proximally of the tissue receiving port, wherein the metallic proximal needle segment provides a proximal cutter lumen segment communicating with the distal cutter lumen segment, wherein the proximal needle segment has a distal end;

- wherein the distal end of the proximal needle segment is positioned distally of the proximal end of the distal needle segment.

20. (previously amended) The biopsy device of Claim 19 wherein a portion of the distal needle segment is molded over a portion of the proximal needle segment.